





# DLA-30-ACF-60 AC Frequency Meter

## Digital Panel Meters



Input: 40 - 90 HZ  
120 / 240VAC

Hertz



Digital AC Frequency Meter with 3.5 digit red high intensity LED. Frequency, 50 or 60 Hertz.

Marine – Ideal for ship to shore panels.

Generators – Ideal for generator panels.

### Specifications

#### Display

Numeral size: 0.56" red high Intensity digits with terminal blocks (isolated design).

Polarity: automatic, "-" displayed.

Overrange: three lower order digits blank for inputs > 1999 & < -1999.

#### Performance:

Range: 50 or 60 Hertz.

Auxiliary Power: 12-24 VDC.

Accuracy:  $\pm(0.05\% \text{ FS} + 1 \text{ count})$ .

Sample rate: 3 readings per second.

Field adjustable: single turn potentiometer for calibration.

Warm-up: 10 minutes typical.

Temperature coeff.:  $\pm 100 \text{ ppm per } ^\circ\text{C}$  typical.

Power Supply Voltage: 12-24 VDC.

#### Environment:

Operating temperature:  $-10 \text{ to } 50 \text{ } ^\circ\text{C}$

Storage temperature:  $-40 \text{ to } 75 \text{ } ^\circ\text{C}$ .

#### Connection:

Terminal Block Connections. Spade terminals.

NOTE: manufactured part numbers have changed. DMC-30-ACF-60 has been replaced by DLA-30-ACF-60.