





DLA-30-DCA-200-100 DC Ammeter

Digital Panel Meters



Range: 0 - 199 ADC
Input: 0 - 100 mVDC
(Shunt rated)



Digital DC Ammeter with 3.5 digit red high intensity LED.

Range: 0-199 ADC, 0-100 mVDC input.

Used with Type LB 200 mV Current Shunt
(LB-200-100, 200 Amp, 100 mV).

Marine – Ideal for ship to shore panels.

Generators – Ideal for generator panels.

Specifications

Display

Numeral size: 0.56" red high Intensity digits with terminal blocks (isolated design).

Polarity: automatic, "-" displayed.

Overrange: three lower order digits blank for inputs > 1999 & < -1999.

Performance:

Range: 0-199 ADC, 0-100 mVDC input.

Auxiliary Power. 12-24 VDC.

Accuracy: $\pm(0.05\% \text{ FS} + 1 \text{ count})$.

Sample rate: 3 readings per second.

Field adjustable: single turn potentiometer for calibration.

Warm-up: 10 minutes typical.

Temperature coeff.: $\pm 100 \text{ ppm per } ^\circ\text{C}$ typical.

Power Supply Voltage: 12-24 VDC.

Environment:

Operating temperature: -10 to 50 °C

Storage temperature: -40 to 75 °C.

Connection:

Terminal Block Connections. Spade terminals.

NOTE: manufactured part numbers have changed. DMC-30-DCA-200-100 has been replaced by DLA-30-DCA-200-100