Model 1131 IN



Analog (1kV below) Insulation Tester

Features

- Hight quality Taut Band movement.
 Three insulation test voltages (DC): 250V, 500V, 1000V.
- Two ranges for continuity test : $2\Omega \& 20\Omega$.
- Compact and lightweight.
- AC voltmeter with linear scale up to 600Vac.
 200mA continuity short-circuit current.
- 1mA test current on insulation test at nominal voltage.
- Automatic discharge of capacitive and inductive circuit with charge stored in the circuit under test.
- Live warning and display of external voltage presence.
- Fuse, air gap, crowbar and overload protected.
- On line battery monitoring shows if battery is ok.
- Manual zero óhm adjustment.
- Low battery consumption.
- Mirror scale.
- Push and turn locking switch for continuous and hand free testing.
- BS 16 edition.

Specifications

Insulation Resistance

Test voltage (DC V)	250V / 500V / 1000V
Output voltage on open circuit	Rated test voltage +10%
Measuring ranges	$0\text{-}100\text{M}\Omega$ / $0\text{-}200\text{M}\Omega$ / $0\text{-}400\text{M}\Omega$
Mid-scale value	$1M\Omega$ / $2M\Omega$ / $4M\Omega$
Scale multiplier	×1/2 / ×1 / ×2
Accuracy	± 5% of indicated value
Output short- circuit current	≥ 1.0mA

Continuity

Measuring ranges	2Ω / 20Ω
zero Ω adjustment by knob	\checkmark
Output short- circuit current	≥ 200 mA
Accuracy	± 1.5% of scale length

AC Voltage

Range	0-600V AC
Accuracy	± 3% of scale length

General

Voltage warning	Warning light circuit live lit From 90Vdc / 70Vac, Buzzer beep from 24V ac/dc
Battery check	Battery check indicate good batteries from 8.5Vdc to 13Vdc during a load test of 250mA.
Battery OK	Battery OK LED lit from 8.5Vdc and is operative while testing.
Dimensions	175(L) × 85(W) × 75(D)mm
Weight (battery included)	Approx. 650g
Power source	1.5V (AA) × 8
Safety standard	EN 61010-1 CAT III 600V, EN 61326-1



AL-24-5



AL-21C2-4



CAC-1132



Accessories

Instruction manual Test leads Shoulder belt **Batteries** Soft pouch (Optional)

Hoyt Electrical Instrument Works, Inc.

23 Meter Street Penacook, NH 03303 Phone: (800) 258-3652 (603) 753-9592 Fax:

Email: sales@hoytmeter.com

www.hoytmeter.com

Page 1 (1)