



Model 2330 LX

Light Meter



CE

2330 LX Light Meter

Features

- Wide range of measurements, up to 40000 lux and 4000 fc
- 0.01 lux and 0.001 fc resolution for accurate low- light measurements
- Light sensor cover is included for preserving sensor life
- Auto off function
- Data hold function
- Low battery indication
- Over range indication
- Auto or manual ranging
- Calibration mode is provided
- 9V battery system
- Selection key for lux or fc
- Spectral sensitivity close to CIE photopic curve
- Ideal tool for workplace, clean-room and computer room light testing
- Video, photographic, office, classroom, and architectural uses

Specifications

Measuring ranges	39.99 / 399.9 / 3999 / 39990 lux 3.999 / 39.99 / 399.9 / 3999fc
Resolution	0.01 lux - 10 lux 0.001 fc - 1 fc
Accuracy	±(3%rdg+5dgt) Calibrated to standard incandescent lamp, 2856°K.
Display	4000 count LCD
Photo sensor	Silicon photodiode
Operating / storage conditions	0°C ~ 40°C < 80 % R.H. -10°C ~ 50°C < 80 % R.H.
Dimensions	194(L) x 62(W) x 34(D)mm
Weight	Approx. 245g (battery included)
Power source	9V (6F22) × 1
Safety standard	EN 61326-1

Accessories

Instruction manual
Carry case
Battery