



# Model 2950 CL

## AC Clamp Meter (with DCV function)



### 2950 CL AC Clamp Meter (with DCV function)

- Pocket size.
- 4000 counts.
- Full automatic measurement.
  - Voltage measurement.
  - Current measurement.
  - Resistor measurement.
- Data hold function.
- Continuity check.
- Diode measurement.
- Select function.
- Low battery indication.
- Auto off function.
- Flashlight (Auto off in 1 minute).

#### Accessories

- Instruction manual
- Test leads
- Soft pouch
- Battery

### Specifications

#### ACA

Range	Resolution	Accuracy
40A	0.01A	$\pm(2\%rdg+5dgt)$
400A/1000A	0.1A/1A	(40~200Hz)

#### ACV

Range	Resolution	Accuracy
4V	1mV	$\pm(1.5\%rdg+10dgt)$ (40~500Hz)
40V	10mV	$\pm(1.5\%rdg+5dgt)$ (40~500Hz)
400V	100mV	
750V	1V	

#### DCV

Range	Resolution	Accuracy
4V	1mV	$\pm(1\%rdg+5dgt)$
40V	10mV	
400V	100mV	
1000V	1V	

#### Resistance

Range	Resolution	Accuracy
400Ω	0.1Ω	$\pm(1.5\%rdg+3dgt)$
4kΩ	1Ω	
40kΩ	10Ω	
400kΩ	100Ω	
4MΩ	1kΩ	
40MΩ	10kΩ	$\pm(2.0\%rdg+4dgt)$

#### Continuity Test

Range	Audible threshold
400Ω	Less than 25Ω

Overload Protection	AC V : 750Vrms DC V : 1000V Diode & ohm : 250Vrms
Conductor size	35mm Max.
Low battery indication	Sign appears on the display
Response time	Approx. 2 times per second
Temperature & humidity	Operating: 0°C ~ 40°C 80% R.H. Max. Storage: 0°C to 50°C 80% Max.
Battery life	Approx. 100 hours on continuous use
Dimensions	183(L) × 62(W) × 20(D)mm
Weight (battery Included)	Approx. 123g
Power source	CR 2032 (DC 3V) × 1
Safety standard	EN 61010-1 CAT II 600V CAT III 300V EN 61010-2-32 EN 61326-1

Small, lightweight, easy to handle carry & store.

Pocket size

One hand operation



**Hoyt Electrical Instrument Works, Inc.**

23 Meter Street  
Penacook, NH 03303

Phone: (800) 258-3652  
Fax: (603) 753-9592  
Email: sales@hoytmeter.com

[www.hoytmeter.com](http://www.hoytmeter.com)