




Model 4132 IN

Analog (1kV below) Insulation Tester



AL-24-5



AL-21C2-4

Accessories

- Instruction manual
- Test leads
- Shoulder belt
- Batteries

Features

- High quality Taut Band movement.
- Three insulation test voltages(DC) : 250V, 500V, 1000V.
- Two continuity test on "low ohms" : 3Ω & 500Ω.
- Compact and lightweight.
- AC voltmeter with linear scale up to 600 Vac.
- 200mA continuity short circuit current.
- 1mA test current on insulation test at nominal voltage.
- Automatic discharge of capacitive and inductive circuit with charge stored in the circuit under test.
- Live warning and display or external voltage presence.
- Fuse, air gap, crowbar and overload protected.
- On line battery monitoring shows if battery is ok.
- Manual zero ohm adjustment.
- Low battery consumption.
- Mirror scale.
- Push and turn locking switch for continuous and hand free testing.
- Designed to meet international standards.
- Supplied with high quality test leads.
- BS 16 edition.

Specifications

Insulation Resistance

Test voltage (DC V)	250V / 500V / 1000V
Output voltage on open circuit	Rated test voltage +10%
Measuring ranges	0-100MΩ / 0-200MΩ / 0-400MΩ
Mid-scale value	1MΩ / 2MΩ / 4MΩ
Scale multiplier	×1/2 / ×1 / ×2
Accuracy	± 5% of indicated value
Output short- circuit current	≥ 1.0mA

Continuity

Measuring range	3Ω / 500Ω
Output short- circuit current	≥ 200 mA
Accuracy	± 1.5% of scale length

AC Voltage

Range	0-600V AC
Accuracy	± 3% of scale length

General

Voltage warning	Warning light circuit live lit From 90Vdc / 70Vac, Buzzer beep from 24V ac/dc
Battery check	Battery check indicate good batteries from 8Vdc to 13Vdc during a load test of 205mA.
Battery OK	Battery OK LED lit from 6.5Vdc and is operative while testing.
Dimensions	250(L) × 190(W) × 110(D)mm
Weight (battery included)	Approx. 1400g
Power source	1.5V (AA) × 8
Safety standard	EN 61010-1 CAT III 600V, EN 61326-1