Model 6210A IN





Features

- Microprocessor-controlled.
- Four insulation test voltages.
- Insulation resistance, auto ranging on all ranges.
- Bargraph indicates test voltage; rise and decay can be observed during tests.
- Visual and audible warning if external voltage is present.
- Fully protected: crow bar.
- Carry case.
- EEPROM calibration.

Accessories

Instruction manual Test leads Shoulder belt Batteries.




AL-30AG

AL-23CAB

Specifications

	Test voltage (DC V)	0.5kV / 1kV / 2.5kV / 5kV
	Measuring ranges (Auto-Ranges)	0-25GΩ / 0-50GΩ / 0-125GΩ / 0-250GΩ
	Accuracy	±3% rdg
	Output power limit	50uA to 100uA (1W)
	Live warning	> 500V AC
	Operation temperature	0°C to 40°C
	Operation-humidity	80% Max. relative humidity
	Dimensions	330(L) × 260(W) × 160(D)mm
	Weight	Approx. 3500g (battery included)
	Power source	1.5V(AA) × 8 Alkaline batteries
	Safety standard	EN 61010-1, EN 61326-1



Hoyt Electrical Instrument Works, Inc.

23 Meter Street Penacook, NH 03303 Phone: (800) 258-3652

(603) 753-9592 Email: sales@hoytmeter.com www.hoytmeter.com

Page 1 (1)