



## 3 Wire Analog Earth Resistance Tester



- High quality Taut Band movement.
- Capable of measuring earth resistance and earth voltage.
- The timer operates automatically for about three to five minutes when the "PUSH BUTTON SWITCH" and "TIMER ON BUTTON" are pressed together.
- This will keep test "ON" for the duration of the timer.
- Battery check function.
- Calibration performed with supplied test leads.

 $\epsilon$ 

## **Specifications**

opecifications	
Measuring ranges	Earth resistance: $0-10\Omega$ / $0-100\Omega$ / $0-1000\Omega$ Earth voltage: $0-30$ Vac ( $40-500$ Hz)
Accuracy	Earth resistance ±3% of full scale Earth voltage ±2.5% of full scale
Measuring system	Earth resistance by constant current inverter 820 Hz, 2mA approx.
Open circuit indication	LED will be unlit
Dimensions	163(L) × 100(W) × 50(D)mm
Weight (battery included)	Approx. 460g
Power source	1.5V (AA) × 6
Safety standards	EN 61010-1 CAT II 30V



AL-36

## **Accessories**

Instruction manual
Test leads (red-15m, yellow-10m, green-5m)
Auxiliary earth spikes
Carry case
Batteries





TEL-1505 S

TOC-1505

Hoyt Electrical Instrument Works, Inc.

23 Meter Street Penacook, NH 03303 Phone: (800) 258-3652 Fax: (603) 753-9592 Email: sales@hoytmeter.com www.hoytmeter.com

Page 1 (1)